



▲ Portable
Electrocardiograph



▲ Blood Glucose Meter and more...

Micro USB Connectors



ZX

Micro USB 2.0 Connector




CX

USB Type-C Connector
USB4 Gen2




CX
SERIES

Micro Coaxial Connectors



U.FL

Mated Height:
1.9mm
(2.5mm Max.)
Applicable Cable:
ø0.81/0.95/1.13/
1.32/1.37mm



X.FL

Mated Height:
0.94mm (1.0mm Max.)
/1.2mm (1.3mm Max.)
Applicable Cable:
ø0.5/0.64/
0.81/1.13mm

RF Switch



MS-180


RF Switch for Module
Functionality Inspection
Height: 0.85mm
Frequency: DC to
11GHz
V.S.W.R.: 1.4 Max.

Low Profile Stacking Connectors



BM25

Pitch: 0.4mm
Mated Height:
0.7mm
Depth: 2.6mm
No. of Pos.:
4(Signal)
2(Power Supply)
Rated Current: 10A



DF37

Pitch: 0.4mm
Mated Height:
0.98/1.5mm
Depth: 2.98mm
No. of Pos.: 10-70
Rated Current: 0.3A

FPC/FFC Connectors



FH34

Top/Bottom Contact
Front Flip
Pitch: 0.5mm
Height: 1.0mm
Depth: 3.8mm
No. of Pos.: 4-50
Rated Current: 0.5A

FH



FH72OneAction FH

Top Contact
One Action
Pitch: 0.3mm
Height: 0.9mm
Depth: 3.5mm
No. of Pos.: 11, 21, 31
Rated Current: 0.2A



FH58

Top/Bottom Contact
Pitch: 0.2mm
Height: 0.9mm
Depth: 3.1mm
No. of Pos.: 21-51
Rated Current: 0.2A

FH