





## Board-to-Board Connector

**FX10**


15+Gbps High Speed  
Pitch: 0.5mm  
Stacking Height:  
4.0-13.0mm  
No. of Pos.: 40-280  
Rated Current: 0.3A

**FX11**

10+Gbps High Speed  
Pitch: 0.5mm  
Stacking Height:  
2.0-3.0mm  
No. of Pos. :  
80/8-140/14  
(Signal Pos./ Ground Pos.)  
96-168 (Without Ground Plate)  
Rated Current: 0.3A

**ER8**


10+Gbps High Speed  
Pitch: 0.8mm  
Stacking Height:  
7.0-12.0mm  
No. of Pos.: 10-120  
Rated Current: 0.5A

**DF12N**

Pitch: 0.5mm  
Stacking Height:  
3.0-5.0mm  
No. of Pos.: 10-80  
Rated Current: 0.3A


**DF57H**

Pitch: 1.2mm  
Height: 1.4mm  
Depth: 4.65mm  
No. of Pos.: 2-6  
Rated Current: 3A Max.  
Applicable Cable:  
26-34 AWG

**DF61Y**

Pitch: 2.2mm  
Height: 2.0mm  
Depth: 7.35mm  
No. of Pos.: 2  
Rated Current: 4A Max.  
Applicable Cable:  
24-28 AWG

## Interface Connector

**ix Industrial™**

IEC Standard  
Cat.6A Ethernet  
Rated Current:  
1.5A (All pins)  
3A (No.1, 2, 6, 7 only)  
Applicable Cable :  
22-28 AWG

**GT17H**

High Speed (DC to 1Gbps)  
No. of Pos.: 4  
Rated Current:  
1A (Signal)  
Applicable Cable:  
24-28 AWG

**HR30**

IP67, IP68  
Small Plastic Connector  
Outer Dia. :  
ø15.5mm Max.  
No. of Pos.: 3, 6, 10, 12  
Rated Current:  
5A (3pos.)  
2A (6, 10, 12pos.)  
Applicable Cable:  
26-30 AWG


**RP13**

Light Weight and Robust  
No. of Pos.: 13, 15, 20  
Rated Current:  
-Standard:  
2A (24 AWG Min.)  
-Anti-Static Type:  
2A (22 AWG Min.)  
Applicable Cable: 18-30 AWG


**DH**

High Speed 2.5Gbps  
Pitch: 1.0mm  
No. of Pos.: 17-51  
Rated Current: 0.5A

## FPC/FFC Connector

**FH52K**

Bottom Contact  
125°C Heat Resistance  
Pitch: 0.5, 1.0mm  
Height: 2.0mm  
Depth: 5.7mm  
No. of Pos.: 6-80  
Rated Current: 0.5A

**FH28K**

Bottom Contact  
Robust  
Pitch: 0.5mm  
Height: 2.55mm  
Depth: 7.2mm  
No. of Pos.: 10-80  
Rated Current: 0.5A