



SPECIFICATION

Current Rating : 16A AC/DC
 Voltage Rating : 250V AC/DC
 Operation Temperature : -40°C to +120°C
 Contact Resistance : 20mΩ max.
 Insulation Resistance : 500MΩ Min.
 Wire Range : 22-14AWG 1.5mm²
 Withstand Voltage : 2000V AC/minute

Mechanical

Torque : 0.4Nm
 Strip length : 4.5-5mm
 Soldering : +250°C Max for 5 sec
 Pitch : 5mm
 Poles : 2-24p

Housing

Screws : PA66, UL94V-0
 Pin Header : M2.5 Steel, Zn Plated
 Pin Header : Copper Alloy, Sn plated
 Shrapnel : Stainless steel

		linear dimension(Tolerances Standard GB/T 14486-2008)										≡	—	□	//	⊥
variable range	to 6	over 6 to 10	over 10 to 18	over 18 to 30	over 30 to 50	over 50 to 80	over 80 to 120	over 120 to 160	over 160 to 200	over 200 to 250	over 250 to	all	to 5	over 5 to 30	over 30 to 120	over 120 to
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4

RoHS Compliant

Taicom TBV8xxAG

Title : Vertical, 5mm Pitch, Wireguard, Solid Block

Tolerance (Unless Specified) : .x = ±0.20
.xx = ±0.15

Dim : (mm)

Angle :